### Need Help? Email: support@betachek.com

# BETACHEK® C50 All-in-One Blood Glucose Meter Quick Start Guide








#### **Contents**

# **Parts summary**



Preparing the meter

Setting the time and date

Run a test

Connecting to the App

Clean the Meter E-4, E-5, E-9, E-12

**Key to Error Messages** 


### **Parts summary**



7. Lancet


8. Lancet ejector

- 1. Sensor cover
- 2. Display
- 3. Sample/settings button
- 4. Memory recall button
- 5. Penetration depth selector
- 6. Lancet holder




- 9. Test Cassette
- 10. Thumbwheel
- 11. Battery cover
- 12. Lancet cover
- 13. Penetration depth indicator
- 14. Sensor

### Preparing the meter



Slide the sensor cover to the left as far as it will go. Meter will turn on.








# 5 Insert lancet and twist off the cap




# Close lancet cover and set desired penetration depth




# Setting the time & date Sideo 1

Hold down the S button to enter the settings menu.





Press M to change the flashing character. Press S to save.





### Connecting to the App (Optional)

Download the App to your mobile device.

€Video 4




BETACHEK Diabetes Management App
Apple and Android





Hold down the S + M buttons until the pairing symbol\* appears.




### Run a test













Press depth selector firmly against selected puncture site, then press S\*





- Gently squeeze out a small round drop of blood.
- Keep the palm of your hand facing down.
- Use immediately. Do not allow the drop to run, dry or spread.









Do not spread blood off the edge of the tape and onto the meter.



See Cleaning the Meter.



Do not smear a small drop across the test zone. A larger drop should be used.








Close the sensor cover. The meter will turn off.

NOTE: If you close the cover before winding the used test away E-3 will be displayed - open the cover and wind



# Cleaning the Meter E-4, E-5, E-9, E-12

Remove the cassette: Push on the curved grip + lift out from the top.

Clean the meter if you spread blood off the tape and onto the

meter or if you

get any of the

above error

messages

Removing a casset

Clean sensor window with a damp cotton tip or tissue in the direction shown.



# **Key to Common Error Messages**

	Head toot not wound into weets
	Used test not wound into waste
	chamber.
	Open sensor cover and wind away
	the used test.
	Blood applied too early or Sensor
	window dirty.
<b>L</b>	Wait for blood drop icon before
	applying blood or clean meter.
	Sensor window dirty or too much direct sunlight.
<b>-</b>	I direct sunlight.
	Clean the meter or move to shade.
	Cassette wound too far. Continue winding until meter says
と一と	Continue winding until meter says
	"OK"
	Insufficient blood.
<b>-</b> -	Use a larger drop or press down on
•	<u> </u>
	the drop to spread it.
,— ,—	Test zone error or Sensor window
	dirty.
	Clean the sensor window and repeat
	the test.
	Expired cassette.
	Cassette past expiry date or opened
ехр	longer than 90 days or date set in
90	meter is a future date - check year.
exp	



- The BETACHEK C50 meter and lancing device are intended for personal use only. Not for multi-patient use.
- The BETACHEK C50 is covered by a 5 Year Warranty from date of purchase. The warranty does not apply to accidental damage, normal wear and tear or if the meter is misused. To claim your warranty please contact: support@betachek.com
- This Quick Start Guide does not replace the user manual which contains important additional information.





